

# Generator de curent stationar cu automatizare la pornire



Generator	SCDE 19YS
Putere max. generator	19 kVA / 15 kW
Putere generator continua	17 kVA / 13.60 kW
Voltaj	400 / 230 V
Frecventa	50 Hz
Factor de putere	0,8
Amperaj	24,5 A
Panou ATS	Inclus in standard
Motor	IND485D
Putere motor	25 cp
Turatie motor	1.500 rpm
Nr. cilindri motor	4 vertical in linie
Aspirare aer	Normala
Preincalzire motor	Inclus in standard
Racire motor	Lichid racire
Capacitate lichid racire	5.4 l
Carburant	Motorina
Consum combustibil	≤ 235 g / kW / h
Autonomie la 70% putere	26 ore
Capacitate rezervor	80 l
Tip ulei	15W40 / 15W50
Capacitate rezervor ulei	4 l
Consum maxim de ulei	0,25 %
Numar poli	4
Regulator de tensiune	AVR
Regulator turatie motor	Mecanic
Precizia tensiunii de iesire	± 1%
Tip alternator	Senci S164G14C5
Greutate neta	650 kg
Dimensiuni LxIxh (mm)	1.950 x 900 x 1.050

**Model: SCDE 19YS**



Dotare standard panou cu automatizare

Protectie generator IP32  
Temperatura de lucru -15° + 70°C  
Temperatura depozitare -30°C +80°C

\*Acest model de generator nu poate fi transportat cu rezervorul incarcat peste 10% din capacitatea maxima.

**MAXJONEL SRL**  
CUI: RO21803460; J28/418/2007  
Str. Fratii Buzesti, 76A, Bals, judet Olt, 235100  
Comenzi: 0741 499 499 - 0757 101 819;  
Piese schimb: 0785 850 961  
comenzi@maxjonel.ro; [www.maxjonel.ro](http://www.maxjonel.ro)